

Product sheet

RUKO 54mm diameter high precision HSS-G core drill bit.

Brand: Ruko

Reference: TUR 128054

The Ruko-128054 HSS-G (Ø 54 mm) hole saw is ideal for alloy steels, non-ferrous metals, and plastics. With a material thickness of up to 2.5 mm and a cutting depth of 5 mm, it is resharpenable and requires minimal pressure.

[View product online](#)

Description

The Ruko-128054-HSS-G (Ø 54 mm) hole saw is a high-precision tool designed for drilling in a wide variety of materials. With a material thickness of up to 2.5 mm and a cutting depth of 5.0 mm, this hole saw is ideal for jobs requiring clean and efficient cuts. Its right-hand cutting design allows for optimal performance in industrial and light construction applications.

This tool is especially recommended for alloy steels with hardnesses up to 800 N/mm², as well as cast steel, non-ferrous metals, light metals, plastics, reinforced fabrics, and plasterboard. It is important to note that it is not suitable for hammer drilling. For optimal performance, it is recommended to apply light pressure when starting to drill, maintaining constant pressure and avoiding oscillating movements.

Additionally, the use of coolant is recommended to extend the tool's lifespan.

- Diameter: Ø 54 mm
- Material thickness: up to 2.5 mm
- Cutting depth: 5.0 mm
- Right-hand cutting
- Resharpenable
- Recommended for alloy steels (up to 800 N/mm²)
- Compatible with non-ferrous and light metals
- Not suitable for hammer drilling
- Requires low pressure to start drilling
- Use of coolant recommended

Specifications

High	6,00
Width	6,00
EAN	4007140295095
Manufacturer	Ruko
Weight (kg)	0,3000
Depth	12,00

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 27 September 2026