

Product sheet

RUKO 60mm diameter high precision HSS-G core drill bit.

Brand: Ruko

Reference: TUR 128060

The Ruko-128060 HSS-G (Ø 60 mm) core drill is ideal for alloy steels, non-ferrous metals, and plastics. With a material thickness of up to 2.5 mm and a cutting depth of 5 mm, it is resharpenable and requires minimal pressure.

[View product online](#)

Description

The Ruko-128060-HSS-G (Ø 60 mm) hole saw is a high-precision tool designed for drilling in a wide variety of materials. With a material thickness of up to 2.5 mm and a cutting depth of 5.0 mm, this hole saw is ideal for working with alloy steels, cast steel, non-ferrous metals, light metals, plastics, reinforced fabrics, drywall, and in light construction. Its right-hand cutting design allows for optimal performance and increased durability, and it is also resharpenable to extend its service life.

It is important to note that this tool is not suitable for hammer drilling. It is recommended to apply light pressure when starting to drill, maintaining constant pressure and avoiding oscillating movements.

For optimal performance, the use of coolant is recommended during the drilling process.

- Diameter: Ø 60 mm
- Material thickness: up to 2.5 mm
- Cutting depth: 5.0 mm
- Right-hand cutting
- Resharpenable
- Recommended for alloy steels (up to 800 N/mm² hardness)
- Suitable for steel castings and non-ferrous metals
- Compatible with plastics and reinforced fabrics
- Not suitable for hammer drilling
- Use of coolant recommended

Specifications

High	7,00
Width	7,00
EAN	4007140295156
Manufacturer	Ruko
Weight (kg)	0,3600
Depth	12,00

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 30 September 2026