

Product sheet

RUKO 114mm HSS-CO core drill bit with fine teeth and high durability.

Brand: Ruko

Reference: TUR 126114

The Ruko-126114 core drill is made of HSS-Co 8 bimetal with fine teeth (Ø 114 mm) and a cutting depth of 38 mm. Ideal for alloy steels, stainless steels, and non-ferrous metals. Use with coolant is recommended.

[View product online](#)**Description**

The Ruko-126114 core drill is designed to deliver exceptional performance when cutting demanding materials. With a diameter of 114 mm and a maximum cutting depth of 38 mm, this tool is ideal for working with alloy and non-alloy steels up to 1,000 N/mm², as well as stainless steels and non-ferrous metals. Its HSS Co 8 construction, along with a special steel body and fine teeth, ensures precise and durable cuts, even under challenging conditions.

The right-hand cutting design allows for greater efficiency in the drilling process, while the use of coolant is essential to maintain the correct temperature and extend the tool's lifespan.

The hole saw is supplied without a support shank and comes in a multi-colored cardboard box, suitable for hanging on a Euro hook, facilitating its storage and display.

- **Diameter:** 114 mm
- **Cutting depth:** 38 mm
- **Material:** HSS Co 8
- **Body:** Special steel
- **Toothings:** Fine
- **Cutting:** Right-hand
- **Applications:** Alloy and non-alloy steels, stainless steels, non-ferrous metals
- **Strength:** Up to 1,000 N/mm²
- **Use:** Always with coolant
- **Presentation:** Multi-colored cardboard box

Specifications

High	5,00
Width	16,00
EAN	4007140124661
Manufacturer	Ruko
Weight (kg)	0,4500
Depth	18,00

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 14 September 2026