

Product sheet

RUKO M20 HSS ground tap set for hand tapping, DIN 352, left-hand thread.

Brand: Ruko

Reference: TUR 230200Li

Set of 3 hand taps M DIN 352 HSS, designed for through threads and blind holes in non-alloy steels and non-ferrous metals. Includes roughing, intermediate, and finishing taps. Left-hand thread M20, tolerance ISO 2/6H.

[View product online](#)

Description

The Ruko-230200Li tap set is designed for creating through and blind hole threads in a wide variety of materials, including unalloyed and low-alloy steels with a tensile strength of up to 800 N/mm², as well as malleable cast iron and non-ferrous metals. This set of taps allows for an efficient and precise threading process, as the thread is cut in three stages: roughing, intermediate, and finishing, guaranteeing a high-quality finish and durability.

- **3-Piece Set:** includes roughing, intermediate, and finishing taps.
- **Thread:** Metric DIN ISO 13.
- **Tolerance:** ISO 2/6H.
- **Surface:** bright, facilitating sliding and reducing friction.
- **Cut:** left-hand, ideal for specific applications.
- **Material:** made of ground high-speed steel (HSS).
- **Applications:** suitable for unalloyed steels, low-alloy steels, malleable cast iron, and non-ferrous metals.
- **Maximum resistance:** withstands up to 800 N/mm².
- **Use:** ideal for precision work in workshops and factories.
- **Dimensions:** M20 thread.

Specifications

High	7,00
------	------

Width	7,00
EAN	4007140098474
Manufacturer	Ruko
Weight (kg)	0,4500
Depth	12,00

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

[If you have any questions, contact our support team](#)

Item downloaded on 11 September 2026