

Product sheet

RUKO G DIN 5157 HSS ground tap set for threading G 1 3/4.

Brand: Ruko

Reference: TUR 236134

Set of 2 Ruko-236134 hand taps, made of ground HSS. Designed for through threads and blind holes in steels and non-ferrous metals. Includes roughing and finishing taps, with Whitworth DIN ISO 228 pipe thread.

[View product online](#)

Description

The Ruko-236134 2-piece hand tap set is an essential tool for creating through and blind hole threads in a variety of materials. Designed for use with unalloyed and low-alloy steels with a tensile strength of up to 800 N/mm², as well as malleable cast iron and non-ferrous metals, this set allows for precise and efficient cutting. The thread is tapped in two steps, guaranteeing a high-quality finish and excellent functionality.

- **Model:** Ruko-236134
- **Type:** Set of 2 taps (roughing and finishing)
- **Standard:** G DIN 5157
- **Material:** HSS (high-speed steel) ground
- **Thread:** Whitworth Tube DIN ISO 228
- **Tolerance:** ISO 2/6H
- **Surface:** Bright
- **Cut:** Right-hand
- **Applications:** Unalloyed steel, low-alloy steel, malleable cast iron, non-ferrous metals
- **Strength Maximum:** 800 N/mm²

This tap set is ideal for professionals who require precision and durability in their threading work.

Specifications

EAN	4007140095060
Manufacturer	Ruko
Weight (kg)	0,5600

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

[If you have any questions, contact our support team](#)

Item downloaded on 14 September 2026