

Product sheet

RUKO BSW 3/4" DIN 352 HSS ground tap set for hand tapping

Brand: Ruko

Reference: TUR 246034

Ruko-246034 3-piece tap set for hand tapping, BSW ~ DIN 352 HSS. Ideal for unalloyed steels and non-ferrous metals. Includes roughing, intermediate, and finishing taps. Packaged in a plastic case with a hanger.

[View product online](#)

Description

The Ruko-246034 3-piece hand tap set is an essential tool for creating through and blind hole threads in a variety of materials, including unalloyed and low-alloy steels with a tensile strength of up to 800 N/mm², as well as malleable cast iron and non-ferrous metals. This set allows for a three-stage tapping process: roughing, intermediate, and finishing, ensuring a precise and high-quality result. The thread is designed according to the Whitworth BSW standard, formerly known as DIN11, and meets ISO 2/6H tolerance, ensuring a perfect fit in industrial applications.

- **Material:** HSS (High Speed Steel) Ground
- **Thread Type:** Whitworth BSW
- **Maximum Strength:** 800 N/mm²
- **Tapping Process:** 3 steps (roughing, intermediate, finishing)
- **Tolerance:** ISO 2/6H
- **Surface Finish:** Bright
- **Cut:** Right-hand
- **Packaging:** Plastic box with hanger
- **Applications:** Unalloyed steel, low-grade steel alloy, malleable cast iron, non-ferrous metals
- **Dimensions:** 3/4" thread

Specifications

EAN	4007140045379
Manufacturer	Ruko
Weight (kg)	0,4300

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

[If you have any questions, contact our support team](#)

Item downloaded on 22 October 2026