

Product sheet

RUKO 3-piece HSS ground tap set for 9/16 UNC DIN 352 threading

Brand: Ruko

Reference: TUR 246916UNC

Ruko-246916UNC 3-piece tap set for hand tapping, designed for non-alloy steels and non-ferrous metals. Includes roughing, intermediate, and finishing taps. American UNC thread, 2B tolerance, bright surface, and right-hand cut.

[View product online](#)

Description

The Ruko-246916UNC tap set is designed for creating through and blind hole threads in a variety of materials, including unalloyed and low-alloy steels with a tensile strength of up to 800 N/mm², as well as malleable cast iron and non-ferrous metals. This set of taps allows for an efficient and precise threading process, as the thread is cut in three stages: roughing, intermediate, and finishing, guaranteeing a high-quality final result.

- **Thread Type:** American UNC, coarse thread
- **Tolerance:** 2B
- **Surface Finish:** Bright
- **Cut:** Right-hand
- **Material:** HSS (High-Speed Steel), ground
- **Applications:** Suitable for unalloyed steels, low-alloy steels, malleable cast iron, and non-ferrous metals
- **Maximum Tensile Strength:** 800 N/mm²
- **Contents:** Set of 3 pieces (roughing, intermediate, and finishing)
- **Presentation:** Plastic box with hanger

This tap and die set is an essential tool for professionals who require precision and durability in their threading work.

Specifications

EAN	4007140100214
Manufacturer	Ruko
Weight (kg)	0,2000

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, [contact our support team](#)

Item downloaded on 14 September 2026