Product sheet



RUKO HSS ground progressive thread tap M5, DIN 352, high precision.

Brand: Ruko

Reference: TUR 231050

M5 progressive thread tap, DIN 352, made of ground HSS. Ideal for through threads in non-alloy steels and non-ferrous metals. Presented in an individual plastic case, with ISO 2/6H tolerance and a bright finish.

View product online

Description

The Ruko-231050 is a progressive thread tap designed for creating through threads in a variety of materials, including unalloyed and low-alloy steels with a tensile strength of up to 800 N/mm², as well as malleable cast iron and non-ferrous metals. This tap allows for single-step thread tapping, either manually or using machines, making it a versatile and efficient tool for machining operations.

- **Thread Type:** Metric DIN ISO 13
- **Tolerance:** ISO 2/6H
- **Surface Finish:** Bright
- **Cut:** Right-handed
- **Compatible Materials:** Unalloyed steels, low-alloy steels, malleable cast iron, and non-ferrous metals
- **Maximum Tensile Strength:** 800 N/mm²
- **Use:** Single-step tapping, manual or mechanical
- **Presentation:** 1 piece per unit
- **Packaging:** Individual plastic case with hanger
- **Applications:** Ideal for machining and parts manufacturing

The Ruko-231050 is an essential tool for professionals seeking precision and durability in their threading projects.

Specifications

High	1,00
Width	1,20
EAN	4007140024275
Manufacturer	Ruko
Weight (kg)	0,0100
Depth	9,40

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 28 November 2026