

Product sheet

RUKO HSS ground progressive thread tap M6 - DIN 352, high precision.

Brand: Ruko

Reference: TUR 231060



Ruko-231060 is an M6 progressive thread tap, made of ground HSS. Ideal for through threads in unalloyed steels and non-ferrous metals. It has a bright surface and is supplied in an individual plastic case.

[View product online](#)

Description

The Ruko-231060 is a progressive thread tap designed for creating through threads in a variety of materials, including unalloyed and low-alloy steels with a tensile strength of up to 800 N/mm², as well as malleable cast iron and non-ferrous metals. This tap allows for single-step thread tapping, either manually or using machines, ensuring a precise and efficient finish. Its high-quality construction ensures optimal performance in industrial and DIY applications.

- **Thread:** Metric DIN ISO 13
- **Tolerance:** ISO 2/6H
- **Surface:** Bright
- **Cut:** Right-hand
- **Material:** Ground HSS
- **Applications:** Unalloyed steel, low-alloy steel, malleable cast iron, non-ferrous metals
- **Use:** Single-step tapping, manual or mechanical
- **Packaging:** 1 piece in individual plastic box with hanger
- **Maximum resistance:** 800 N/mm²

This tap is an essential tool for those seeking precision and durability in their threading work.

Specifications

High	1,00
Width	1,20
EAN	4007140024282
Manufacturer	Ruko
Weight (kg)	0,0100

Depth	9,40
-------	------

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

[If you have any questions, contact our support team](#)

Item downloaded on 5 October 2026