

Product sheet

RUKO HSS-Co 5 ground thread tap M3 DIN 352, high precision and durability.

Brand: Ruko

Reference: TUR 231030E



M3 progressive thread tap, made of HSS-Co 5 high-speed steel, ideal for through threads in unalloyed steels and non-ferrous metals. It has a bright surface and is supplied in an individual plastic case.

[View product online](#)

Description

The Ruko-231030E progressive thread tap is a high-precision tool designed for creating threads in a variety of materials. Made from cobalt alloy high-speed steel, this tap offers exceptional heat resistance, resulting in a long tool life and superior performance in demanding applications. It is ideal for through threads in unalloyed and low-alloy steels with a tensile strength of up to 900 N/mm², as well as in malleable cast iron and non-ferrous metals. Its design allows the thread to be tapped in a single step, either by hand or machine, facilitating its use in different work environments.

- **Material:** Cobalt alloy high-speed steel
- **Heat resistance:** High, for long service life
- **Applications:** Unalloyed steel, low-alloy steel, malleable cast iron, and non-ferrous metals
- **Thread type:** Metric DIN ISO 13
- **Tolerance:** ISO 2/6H
- **Surface:** Bright
- **Cut:** Right-handed
- **Use:** Single-step tapping, manual or mechanical
- **Packaging:** Individual plastic box with hanger
- **Quantity:** 1 piece

Specifications

High	1,00
Width	3,00
EAN	4007140095152
Manufacturer	Ruko
Weight (kg)	0,0100

Depth	7,50
-------	------

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

[If you have any questions, contact our support team](#)

Item downloaded on 14 September 2026