

Product sheet

RUKO HSS ground tap type CM 2.5 DIN 371, high precision.

Brand: Ruko

Reference: TUR 234025



Ruko-234025 machine tap, type C, with reinforced shank and 35° spiral flutes. Ideal for threading blind holes in non-alloy steels and non-ferrous metals. Includes individual plastic case with hanger.

[View product online](#)

Description

The Ruko-234025 tap is a high-precision tool designed for creating threads in blind holes. Made of high-speed steel (HSS) with a reinforced shank, this tap features 35° spiral flutes that facilitate efficient and clean cutting. It is ideal for working with unalloyed and low-alloy steels, as well as malleable cast iron and non-ferrous metals, withstanding a tensile strength of up to 800 N/mm². The thread is cut in a single step, guaranteeing a quality and precise finish every time.

- **Model:** Ruko-234025
- **Type:** Machine tap
- **Thread:** Metric DIN ISO 13
- **Tolerance:** ISO 2/6H
- **Surface:** Bright
- **Cut:** Right-hand
- **Applications:** Blind holes in unalloyed steels, low-alloy steels, malleable cast iron, and non-ferrous metals
- **Maximum strength:** 800 N/mm²
- **Contents:** 1 piece
- **Presentation:** Individual plastic box with hanger

Specifications

High	1,00
Width	1,20
EAN	4007140096869
Manufacturer	Ruko
Weight (kg)	0,0100

Depth	9,30
-------	------

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

[If you have any questions, contact our support team](#)

Item downloaded on 19 October 2026