

Product sheet

RUKO M18 HSS ground type C tap, DIN 376, high precision.

Brand: Ruko

Reference: TUR 233180



M18 Type C tap, made of ground HSS. Designed for blind holes in non-alloy steels and non-ferrous metals. Features a reinforced shank and 35° spiral flutes. Includes individual plastic case with hanger.

[View product online](#)

Description

The Ruko-233180 tap is a high-precision tool designed for creating threads in blind holes. Made of high-speed steel (HSS) with a reinforced shank, this tap features 35° spiral flutes that optimize the cutting process, ensuring a superior finish. It is ideal for working with unalloyed and low-alloy steels with a tensile strength of up to 800 N/mm², as well as malleable cast iron and non-ferrous metals. The thread is cut in a single step, making it easy to use and improving work efficiency.

- **Model:** Ruko-233180
- **Type:** Machine tap
- **Thread:** Metric DIN ISO 13
- **Tolerance:** ISO 2/6H
- **Surface:** Bright
- **Cut:** Right-handed
- **Applications:** Blind holes in unalloyed steels, low-alloy steels, malleable cast iron, and non-ferrous metals
- **Maximum strength:** 800 N/mm²
- **Packaging:** Individual plastic box with hanger
- **Units:** 1 piece

Specifications

High	2,50
Width	3,00
EAN	4007140024480
Manufacturer	Ruko
Weight (kg)	0,1400

Depth	12,70
-------	-------

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

[If you have any questions, contact our support team](#)

Item downloaded on 27 October 2026