

Product sheet

RUKO HSS-Co 5 M 2.5 DIN 371 type C tap, high precision ground.

Brand: Ruko

Reference: TUR 234025E



Ruko-234025E Type C Machine Tap. Made of HSS-Co 5 high-speed steel, ideal for M 2.5 threads in blind holes. Includes reinforced shank and spiral flutes. Packaged in an individual plastic case with a hanger.

[View product online](#)

Description

The Ruko-234025E tap is a high-precision tool designed for creating threads in blind holes. Made of cobalt alloy high-speed steel, this tap offers exceptional heat resistance, resulting in a long service life and optimal performance in various industrial applications. Its design includes a reinforced shank and 35° spiral flutes, which facilitate cutting and improve chip evacuation during the tapping process.

This tap is ideal for working with unalloyed and alloyed steels with a tensile strength of up to 800 N/mm², as well as malleable cast iron and non-ferrous metals. The thread is tapped in a single step, ensuring high precision and a quality finish.

It features a bright surface and a right-hand cut, complying with DIN ISO 13 metric standards and ISO 2/6H tolerances.

- **Model:** Ruko-234025E
- **Type:** Machine tap
- **Material:** HSS-Co 5 high-speed steel
- **Thread:** Metric DIN ISO 13
- **Tolerance:** ISO 2/6H
- **Surface:** Bright
- **Cut:** Right-hand
- **Shank:** Reinforced
- **Flutes:** 35° spirals
- **Packaging:** Individual plastic box with hanger

Specifications

High	1,00
Width	3,00
EAN	4007140096883
Manufacturer	Ruko
Weight (kg)	0,0100
Depth	7,50

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 15 October 2026