

Product sheet

RUKO HSS-Co 5 M 4 DIN 371 type C tap, high precision ground.

Brand: Ruko

Reference: TUR 234040E



Ruko-234040E machine tap, made of HSS-Co 5 high-speed steel. Designed for M4 threads in blind holes, with a reinforced shank and spiral flutes. Includes individual plastic case. Ideal for steels and non-ferrous metals.

[View product online](#)

Description

The Ruko-234040E tap is a high-precision tool designed for creating threads in blind holes. Made of cobalt alloy high-speed steel, this tap offers exceptional heat resistance, resulting in a long service life and optimal performance in a variety of industrial applications. Its reinforced shank and 35° spiral flutes ensure efficient and precise cutting, ideal for working with unalloyed and alloyed steels with a tensile strength of up to 800 N/mm², as well as malleable cast iron and non-ferrous metals.

This tap allows for one-step thread blanking, simplifying its use and improving productivity. With a metric thread conforming to DIN ISO 13 and a tolerance of ISO 2/6H, the Ruko-234040E ensures consistent, high-quality results.

Its bright surface not only provides an aesthetic finish, but also contributes to reducing friction during the cutting process.

- **Model:** Ruko-234040E
- **Type:** Machine tap
- **Material:** HSS-Co 5 high-speed steel
- **Thread:** Metric DIN ISO 13
- **Tolerance:** ISO 2/6H
- **Surface:** Bright
- **Cutting:** Right-hand
- **Applications:** Non-alloy steels, alloy steels, malleable cast iron, non-ferrous metals
- **Shank:** Reinforced
- **Presentation:** Individual plastic box with hanger

Specifications

High	0,60
Width	1,20
EAN	4007140058829
Manufacturer	Ruko
Weight (kg)	0,0100
Depth	8,40

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 12 October 2026