

Product sheet

RUKO HSS-Co 5 DIN 374 MF24 x 2 mm tap, type B ground.

Brand: Ruko

Reference: TUR 260242E



Ruko-260242E tap for MF machines, made of HSS-Co 5 high-speed steel. Designed for through threads in steels and non-ferrous metals. Fine metric thread MF24 x 2 mm, with ISO 2/6H tolerance. Packaged in a plastic case.

[View product online](#)**Description**

The Ruko-260242E tap is a high-precision tool designed for machining through threads in a variety of materials. Made of cobalt alloy high-speed steel, this tap offers exceptional heat resistance, resulting in a long tool life and optimal performance under demanding conditions. Its reinforced shank ensures greater stability during the tapping process, allowing for high-quality results in unalloyed and alloyed steels with a tensile strength of up to 900 N/mm², as well as malleable cast iron and non-ferrous metals.

This tap features a right-hand cutting design and the ability to tap threads in a single pass, making it easy to use in industrial and workshop applications.

It features a bright surface that reduces friction and improves cutting efficiency.

- **Model:** Ruko-260242E
- **Type:** Machine tap
- **Material:** HSS-Co 5 high-speed steel
- **Thread:** Fine metric DIN ISO 13
- **Tolerance:** ISO 2/6H
- **Dimensions:** MF24 x 2 mm
- **Cut:** Right-hand
- **Surface:** Bright
- **Use:** Tapping in steels and non-ferrous metals
- **Packaging:** Individual plastic box with hanger

Specifications

High	3,50
Width	10,00
EAN	4007140095701
Manufacturer	Ruko
Weight (kg)	0,3100
Depth	16,00

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 3 October 2026