

Product sheet

RUKO HSS combination machine tap, M5 thread, ground.

Brand: Ruko

Reference: TUR 270016



Ruko-270016 HSS combination tap, ideal for drilling, tapping, cleaning, and countersinking in a single operation. Compatible with unalloyed and alloyed steels up to 600 N/mm². Metric thread DIN ISO 13, ISO 2/6H tolerance, bright finish.

[View product online](#)**Description**

The Ruko-270016 is a combination HSS tap designed for machine tools, allowing multiple operations to be performed with a single tool. This product is ideal for users seeking efficiency and precision in metalworking. Its design allows for drilling, tapping, cleaning, and countersinking, making it a versatile solution for various industrial applications.

Manufactured for working with unalloyed and alloyed steels up to a tensile strength of 600 N/mm², as well as malleable cast iron and non-ferrous metals, the Ruko-270016 is a robust and reliable tool. The thread conforms to the DIN ISO 13 metric standard, with an ISO 2/6H tolerance, ensuring a high-quality finish.

Its bright surface and right-hand cutting edge guarantee optimal performance with every use.

- Material: HSS (High-Speed Steel)
- Thread: Metric DIN ISO 13
- Tolerance: ISO 2/6H
- Surface: Bright
- Cut: Right-hand
- 1/4" Hex Shank
- Compatible with magnetic bit holders (see WITTE 26006)
- For use on unalloyed and alloyed steels up to 600 N/mm²
- Includes individual plastic case with hanger
- Ideal for drilling, tapping, cleaning, and countersinking

Specifications

High	1,00
Width	1,00
EAN	4007140108302
Manufacturer	Ruko
Weight (kg)	0,0100
Depth	10,80

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 26 October 2026