

Product sheet

RUKO HSS ground round bearing M 4 left thread, DIN EN 22568.

Brand: Ruko

Reference: TUR 237040LI

Round bearing M DIN EN 22568 HSS ground with M4 left-hand thread. Designed for non-alloy steels and non-ferrous metals. Bright surface and ISO -6g tolerance. Packaged in an individual plastic box with hanger.

[View product online](#)**Description**

The Ruko-237040LI DIN EN 22568 HSS ground round bearing is a high-precision tool designed for use on unalloyed and low-alloy steels with a tensile strength of up to 800 N/mm², as well as non-ferrous metals. This bearing features a left-hand thread, making it ideal for specific applications requiring a left-hand cut. The thread is tapped in a single step, ensuring optimal quality and finish. Its bright surface not only provides an aesthetic appearance but also improves resistance to corrosion and wear.

- **Thread type:** Left-handed
- **Compatible materials:** Non-alloy steels, low-alloy steels, and non-ferrous metals
- **Maximum strength:** 800 N/mm²
- **Thread:** Metric DIN ISO 13
- **Tolerance:** ISO - 6g
- **Surface:** Bright
- **Cut:** Left-handed
- **Packaging:** Individual plastic box with hanger
- **Quantity:** 1 piece

Specifications

High	2,00
Width	3,50
EAN	4007140101785
Manufacturer	Ruko
Weight (kg)	0,0100
Depth	3,50

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

[If you have any questions, contact our support team](#)

Item downloaded on 17 September 2026