

Product sheet

RUKO HSS ground round bearing M16 left thread DIN EN 22568

Brand: Ruko

Reference: TUR 237160Li

Round bearing M DIN EN 22568 HSS ground with M 16 left-hand thread. Designed for non-alloy steels and non-ferrous metals. Bright surface and ISO - 6g tolerance. Packaged in an individual plastic box with hanger.



[View product online](#)

Description

The Ruko-237160Li round bearing is a high-precision tool designed for use in unalloyed and low-alloy steels, with a tensile strength of up to 800 N/mm², as well as non-ferrous metals. This bearing features a left-hand thread, making it ideal for specific applications where a left-hand cut is required. The thread is tapped in a single step, ensuring superior quality and a perfect fit in your application. Its bright surface not only provides an aesthetic finish, but also improves resistance to corrosion and wear.

- **Model:** Ruko-237160Li
- **Thread Type:** Left-handed
- **Compatible Material:** Non-alloy steels, low-alloy steels, and non-ferrous metals
- **Maximum Strength:** 800 N/mm²
- **Thread:** Metric DIN ISO 13
- **Tolerance:** ISO - 6g
- **Surface:** Bright
- **Cut:** Left-handed
- **Packaging:** Individual plastic box with hanger
- **Quantity:** 1 piece

Specifications

High	2,00
Width	5,50
EAN	4007140101914
Manufacturer	Ruko
Weight (kg)	0,1300
Depth	5,50

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

[If you have any questions, contact our support team](#)

Item downloaded on 1 October 2026