

Product sheet

RUKO HSS ground round bearing type B, MF12 x 1.25 mm thread.

Brand: Ruko

Reference: TUR 239122

MF DIN EN 22568 HSS ground type B closed round bearing, designed for non-alloy steels and non-ferrous metals. MF12 x 1.25 mm thread, ISO - 6g tolerance. Packaged in an individual plastic box with a hanger.

[View product online](#)**Description**

The Ruko-239122 round bearing is an ideal solution for applications requiring high precision and strength. Designed for use in unalloyed and low-alloy steels with a tensile strength of up to 800 N/mm², as well as in non-ferrous metals, this bearing ensures optimal performance under various operating conditions. Its fine metric DIN ISO 13 thread is tapped in a single step, ensuring simple and efficient installation. With an ISO -6g tolerance and a bright finish, this bearing is not only functional but also aesthetically pleasing.

- **Model:** Ruko-239122
- **Type:** Round MF bearing DIN EN 22568 HSS ground type B closed
- **Thread:** MF12 x 1.25 mm
- **Material:** Non-alloy steel, low-alloy steel, and non-ferrous metals
- **Maximum strength:** 800 N/mm²
- **Thread:** Fine metric DIN ISO 13
- **Tolerance:** ISO -6g
- **Surface:** Bright
- **Cutting:** To the right
- **Presentation:** Individual plastic box with hanger

Specifications

High	2,00
Width	4,50
EAN	4007140045560
Manufacturer	Ruko
Weight (kg)	0,0500

Depth	4,50
-------	------

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

[If you have any questions, contact our support team](#)

Item downloaded on 13 September 2026