

## Product sheet

**RUKO type B closed round bearing HSS, MF16 x 1.25 mm thread.**

Brand: Ruko

Reference: TUR 239162

MF DIN EN 22568 HSS ground type B closed round bearing, designed for non-alloy steels and non-ferrous metals. MF16 x 1.25 mm thread, ISO - 6g tolerance. Packaged in an individual plastic box with a hanger.

[View product online](#)**Description**

The Ruko-239162 round bearing is a high-precision solution designed for applications in unalloyed and low-alloy steels, with a tensile strength of up to 800 N/mm<sup>2</sup>, as well as in non-ferrous metals. This component features a fine metric DIN ISO 13 thread, which is tapped in a single step, ensuring efficient and secure installation. Its bright surface not only provides an aesthetic finish but also contributes to corrosion and wear resistance. The right-hand cut ensures a perfect fit in the required applications.

- **Model:** Ruko-239162
- **Type:** Round MF bearing DIN EN 22568 HSS ground type B closed
- **Thread:** MF16 x 1.25 mm
- **Material:** Non-alloy and low-alloy steel, non-ferrous metals
- **Maximum strength:** 800 N/mm<sup>2</sup>
- **Thread:** Fine metric DIN ISO 13
- **Tolerance:** ISO - 6g
- **Surface:** Bright
- **Cut:** Right-hand
- **Presentation:** Individual plastic box with hanger

**Specifications**

|              |               |
|--------------|---------------|
| High         | 2,00          |
| Width        | 5,50          |
| EAN          | 4007140096296 |
| Manufacturer | Ruko          |
| Weight (kg)  | 0,1100        |
| Depth        | 5,50          |

---

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

[If you have any questions, contact our support team](#)

Item downloaded on 14 October 2026