

Product sheet

RUKO type B closed round bearing HSS DIN EN 22568, 5/32" thread

Brand: Ruko

Reference: TUR 247532

BSW-DIN EN 22568 HSS ground type B closed round bearing with 5/32" thread. Designed for non-alloy steels and non-ferrous metals. Packaged in an individual plastic case with a hanger. Ideal for precision applications.

[View product online](#)**Description**

The Ruko-247532 round bearing is a high-precision tool designed for machining unalloyed and low-alloy steels with a tensile strength of up to 800 N/mm², as well as non-ferrous metals. This bearing features a BSW thread, formerly known as DIN 11, and is tapped in one step, ensuring a perfect fit and excellent functionality in industrial applications. Its enclosed design provides greater durability and protection against contaminants, ensuring optimal performance under demanding conditions.

- **Material:** HSS (High Speed Steel) Ground
- **Applications:** Unalloyed and low-alloy steels, non-ferrous metals
- **Maximum strength:** Up to 800 N/mm²
- **Thread:** BSW, formerly DIN 11
- **Type:** Enclosed
- **Manufacturing process:** One-step tapping
- **Packaging:** Individual plastic box with hanger
- **Dimensions:** 5/32" thread
- **Recommended use:** Precision machining
- **Durability:** High wear resistance

This bearing is ideal for professionals looking for superior quality tools for their machining projects.

Specifications

High	2,00
Width	3,50
EAN	4007140045645
Manufacturer	Ruko

Weight (kg)	0,0100
Depth	3,50

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

[If you have any questions, contact our support team](#)

Item downloaded on 29 September 2026