

Product sheet

RUKO type B closed round bearing HSS, 5/16" thread, DIN EN 22568.

Brand: Ruko

Reference: TUR 247516

BSW-DIN EN 22568 HSS ground type B closed round bearing with 5/16" thread. Designed for non-alloy steels and non-ferrous metals. Packaged in an individual plastic box with a hanger for easy storage.

[View product online](#)**Description**

The Ruko-247516 round bearing is a high-precision tool designed for use in unalloyed and low-alloy steels with a tensile strength of up to 800 N/mm², as well as in non-ferrous metals. This bearing features a BSW thread, formerly known as DIN 11, and is tapped in one step, ensuring simple and efficient installation. Its enclosed design provides greater durability and protection against contaminants, making it an ideal choice for industrial and mechanical applications.

- **Model:** Ruko-247516
- **Type:** BSW-DIN EN 22568 HSS ground closed type B round bearing
- **Thread:** 5/16"
- **Material:** High-speed steel (HSS)
- **Applications:** Unalloyed and low-alloy steels, non-ferrous metals
- **Strength:** Up to 800 N/mm²
- **Thread:** Single-step die
- **Standard:** BSW, formerly DIN 11
- **Presentation:** Individual plastic box with hanger
- **Use:** Ideal for industrial and mechanical applications

Specifications

High	2,00
Width	3,50
EAN	4007140045683
Manufacturer	Ruko
Weight (kg)	0,0200
Depth	3,50

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

[If you have any questions, contact our support team](#)

Item downloaded on 30 October 2026