

Product sheet

RUKO HSS ground round bearing type B closed, 2" thread DIN EN 22568.

Brand: Ruko

Reference: TUR 247020

BSW-DIN EN 22568 HSS ground type B closed round bearing, designed for non-alloy steels and non-ferrous metals. 2" thread with one-step tapping. Packaged in an individual plastic box with a hanger.

[View product online](#)**Description**

The Ruko-247020 round bearing is a high-precision tool designed for machining unalloyed and low-alloy steels with a tensile strength of up to 800 N/mm², as well as non-ferrous metals. This bearing features a BSW thread, formerly known as DIN 11, which is tapped in a single step, ensuring an optimal fit and easy installation. Its enclosed design provides greater durability and protection against contaminants, making it a reliable choice for various industrial applications.

- **Material:** Ground High-Speed Steel (HSS)
- **Type:** Closed B
- **Thread:** BSW, formerly DIN 11
- **Capacity:** Accepts unalloyed and low-alloy steels up to 800 N/mm²
- **Applications:** Suitable for non-ferrous metals
- **Packaging:** Individual plastic box with hanger
- **Dimensions:** 2" thread
- **Manufacturing Process:** High-precision grinding
- **Durability:** Enclosed design for greater protection
- **Ease of Use:** One-step tapped thread for quick installation

Specifications

High	2,00
Width	10,50
EAN	4007140045843
Manufacturer	Ruko
Weight (kg)	0,9300
Depth	10,50

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

[If you have any questions, contact our support team](#)

Item downloaded on 16 September 2026