

Product sheet

RUKO type N twist drill with cutting insert, diameter 3.30 mm, DIN 338.

Brand: Ruko

Reference: TUR 815033



Ruko-815033 DIN 338 Type N Twist Drill Bit, 3.30 mm diameter. Made of HSS-G and equipped with a brazed carbide cutting insert. Ideal for drilling high-strength steels with permanent coolant.

[View product online](#)

Description

The Ruko-815033 twist drill bit is a high-precision tool designed to meet the demands of drilling high-strength materials. Made of high-speed steel (HSS-G), this drill bit features a brazed carbide cutting insert, ensuring exceptional durability and performance. Its helical design allows for efficient chip evacuation, optimizing the drilling process and reducing the risk of clogging.

The fine-grained K20 material used in its manufacture makes it suitable for universal use, and particularly effective in high-strength steels.

However, it is important to note that drilling in these materials must be carried out with continuous cooling to ensure optimal performance and extend the tool's lifespan.

- **Diameter:** Ø 3.30 mm
- **Type:** DiN 338 Type N Twist Drill Bit
- **Material:** HSS-G with brazed carbide cutting insert
- **Grain:** K20, suitable for universal use
- **Applications:** Drilling in high-strength steels
- **Cooling:** Required for drilling in high-strength steels
- **Durability:** High, thanks to the carbide cutting insert
- **Chip evacuation:** Efficient, thanks to the helical design
- **Use:** Professional and industrial
- **Compatibility:** Ideal for general purpose drills

Specifications

High	2,00
Width	2,00
EAN	4007140353184
Manufacturer	Ruko
Weight (kg)	0,0100
Depth	6,50

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 17 September 2026