

Product sheet

RUKO type N twist drill with cutting insert, diameter 5.10 mm, DIN 338.

Brand: Ruko

Reference: TUR 815051



Ruko-815051 DIN 338 Type N Twist Drill with Brazed Carbide Cutting Insert (Ø 5.10 mm). Made of HSS-G, ideal for drilling high-strength steels with permanent coolant. Fine-grain K20 material for universal use.

[View product online](#)

Description

The Ruko-815051 twist drill is a high-precision tool designed to meet the demands of drilling high-strength materials. Made of high-speed steel (HSS-G), this drill features a brazed carbide cutting insert, ensuring exceptional durability and performance in industrial applications. Its helical design allows for efficient chip evacuation, optimizing the drilling process and reducing the risk of overheating.

The fine-grained K20 material used in its manufacture makes it suitable for universal use, and particularly effective in high-strength steels.

It is important to note that for drilling in these materials, the use of continuous cooling is recommended, which ensures optimal performance and extends the tool's lifespan.

- **Type:** DiN 338 Type N Twist Drill Bit
- **Diameter:** Ø 5.10 mm
- **Material:** HSS-G with brazed carbide cutting insert
- **Grain:** K20, suitable for universal use
- **Applications:** Drilling in high-strength steels
- **Cooling:** Requires continuous cooling for high-strength steels
- **Durability:** High wear resistance
- **Chip evacuation:** Optimized design for efficient evacuation
- **Use:** Ideal for industrial and mechanical applications
- **Quality:** Manufactured according to quality standards

Specifications

High	3,00
Width	3,00
EAN	4007140353344
Manufacturer	Ruko
Weight (kg)	0,0100
Depth	9,00

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 13 September 2026