

Product sheet

**Polyester thread guide 4.5 mm, interchangeable tip, 20 m, 180 kg pull**

Brand: ATM

Reference: TUR 750020

4.5 mm x 20 m polyester cable guide, designed for areas with continuous curves. Features a flexible steel tip and helical ridges to reduce friction. Withstands a maximum pull of 180 kg. Orange color. M-5 thread.

[View product online](#)**Description**

The ATM-750020 cable pulling guide is a specialized tool designed to facilitate cable laying in areas with continuous curves. Its 4.5 mm diameter polyester construction and interchangeable tip allow for greater adaptability and flexibility, especially in applications requiring sharp turns. The flexible steel pulling tip, equipped with an eyelet, provides superior maneuverability around curve radii, optimizing the installation process.

Thanks to its helical ridge design, this guide exhibits significantly reduced resistance and friction when penetrating the conduit, achieving 60% less internal friction compared to other guides on the market.

This translates into greater efficiency and ease of use during cable laying.

- **Diameter:** 4.5 mm
- **Length:** 20 m
- **Color:** Orange
- **Maximum Tensile Strength:** 180 kg
- **Thread:** M-5
- **Material:** Polyester
- **Tip:** Flexible steel with eyelet
- **Design:** Helical ridges for reduced friction
- **Use:** Areas with multiple continuous pipe bends
- **Flexibility:** High, ideal for bend radii

Specifications

High	3,00
Width	30,00
EAN	8435130725295
Manufacturer	ATM
Weight (kg)	0,4750
Depth	30,00
Cable cross-section (mm²)	4.5

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 21 October 2026