Product sheet



ACTI 9 multifunction TIMER relay 8 A, range 0.1...360000 s, DIN mounting.

Brand: SCHNEIDER

Reference: IMPO A9E16070

The Acti 9 range RTMF timer is a multifunctional relay with a rated current of 8 A and a timing range of 0.1 to 360,000 s. It is DIN rail mounted, has IP20 protection, and operates between -5 and 55 °C.

View product online

Description

The **RTMF TIMER** is a time-delay relay from the Acti 9 range, designed to offer versatile solutions in control and automation applications. This multifunctional device allows for a wide timing range, from 0.1 to 360,000 seconds, adapting to diverse needs in residential and small commercial environments.

The RTMF model features a 1 A/C signaling contact configuration, ensuring reliable and efficient performance. Its rated operating current is 8 A at 250 V AC and DC, and 0.01 A at 5 V DC, making it suitable for a wide range of applications.

Furthermore, its rotary control allows for easy configuration of the timing relay, with four selectable delay types.

Technical features include:

- Mechanical durability: 5,000,000 cycles
- Electrical durability: 100,000 cycles (AC-1, state 1)
- Operating temperature: -5...55 °C
- Protection rating: IP20
- Connections: Tunnel-type terminals for cables up to 2.5 mm²
- Repeatability accuracy: +/- 0.5%
- Micro-interruption immunity: 20 ms
- Dimensions: 93 mm (height) x 18 mm (width) x 72 mm (depth)
- Weight: 0.065 kg
- Color: White

The RTMF TIMER is a reliable and efficient option for controlling timed processes in various applications.

Specifications

Rated current (A)	8
EAN	3606480377464
Manufacturer	Schneider
Reference	SCHNEIDER A9E16070

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 21 November 2026