Product sheet



RCCB SCHNEIDER differential switch 4 poles 25A 300mA type A.

Brand: SCHNEIDER

Reference: IMPO A9R24425

The RCCB_IID 4P 25A 300mA A-type is a 4-pole residual current circuit breaker (RCCB) designed to protect electrical circuits. It offers a rated current of 25A and a sensitivity of 300mA, making it ideal for residential and industrial applications.

View product online

Description

The RCCB_IID 4P 25A 300mA A-type is an electrical protection device designed to detect and prevent current leakage in electrical systems. This four-pole residual current device (RCD) offers a high sensitivity of 300 mA, making it an ideal solution for residential and industrial applications where additional protection against electrical shock is required. Its robust and efficient design guarantees safe and reliable operation, contributing to the safety of electrical installations.

- **Type:** RCCB (Residual Current Circuit Breaker)
- **Poles:** 4 (four)
- **Rated current:** 25A
- **Leakage current:** 300mA
- **Current type:** A (detects alternating and pulsating currents)
- **Rated voltage:** 400V AC
- **Frequency:** 50/60 Hz
- **Protection:** against overloads and short circuits
- **Installation:** easy DIN rail mounting
- **Standards:** complies with IEC 61008-1 regulations

This device is essential to ensure electrical safety in various applications, providing a rapid response to any anomaly in current flow.

Specifications

Rated current (A)	25
Sensitivity	300 mA
EAN	3606480374739

No. of poles	4P
Reference	SCHNEIDER A9R24425

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 30 October 2026