

Product sheet

SCHNEIDER 95A 3-pole 1NO+1NC 24VDC contactor for efficient electrical control.



Brand: SCHNEIDER

Reference: IMPO LC1D95BD

95A 3-pole contactor with one normally open and one normally closed contact, designed for 24VDC operation. Ideal for industrial applications requiring power control and safety in electrical circuits. Meets quality standards.

[View product online](#)

Description

The CONT. 95A 3P 1NO+1NC 24VDC is a high-efficiency contactor designed for industrial applications requiring precise and reliable control of electrical circuits. This device features a robust construction and high-quality components that ensure optimal performance under demanding conditions. Its 3-pole configuration, along with one normally open (NO) and one normally closed (NC) contact, allows for versatile load handling, adapting to diverse operational needs. With a 24VDC supply voltage, this contactor is ideal for automation and control systems, offering a fast and safe response to load variations.

- **Type:** Contactor
- **Configuration:** 3 poles (3P)
- **Contacts:** 1NO + 1NC
- **Supply Voltage:** 24VDC
- **Current Capacity:** 95A
- **Use:** Industrial and automation applications
- **Material:** High-quality components
- **Dimensions:** Compact for easy installation
- **Certifications:** Complies with safety regulations
- **Durability:** Designed for long-term use

Specifications

Rated current (A)	95
EAN	3389110450576
No. of poles	3P
Reference	SCHNEIDER LC1D95BD

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

[If you have any questions, contact our support team](#)

Item downloaded on 3 October 2026