Product sheet



ALTRONIC timer 24-240V AC, 8 A, timing range 1...10 min, DIN mounting

Brand: SCHNEIDER

Reference: IMPO RE22R2AMU

The Harmony RE22 timer is a device designed for controlling electrical circuits within a voltage range of 24 to 240 V AC. Its adjustable timing and relay contacts ensure reliable performance in industrial and commercial applications, adapting to diverse operating conditions.

View product online

Description

The ALTRONIC 24-240V AC timer is a device designed for the efficient control of electrical circuits in industrial and commercial environments. With a voltage range of 24 to 240 V AC, this timer allows for adjustable timing to suit various operational needs, ensuring reliable and accurate performance.

- Product Type: DIN Rail Mounting Timer
- Rated Output Current: 8 A
- Control Circuit Voltage: 24 V, 24...240 V AC
- Output Type: Relay
- Timing Range: 1...10 min, 10...100 H, 1...10 s, 0.1...1 s, 6...60 s, 6...60 min, 1...10 H
- Control Type: Rotary Knob on Front Panel
- Supply Frequency: 50...60 Hz +/- 5 %
- Housing Material: Self-extinguishing
- Electrical durability: 100,000 cycles for resistive at 8 A at 250 V, AC-1
- Operating ambient temperature: -20...60 °C
- Protection rating: IP40 for the housing
- Power consumption: 50 VA at 240 V AC
- Connections: Screw terminals, 2 x 1.5 mm² and 2 x 2.5 mm²

Specifications

Rated current (A)	8

EAN	3606480676567
Nominal voltage (V)	240

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 4 November 2026