

Product sheet



TeSys 63 A IP65 high-performance switch disconnect with lockable handle for harsh environments

Brand: SCHNEIDER

Reference: IMPO VBF4GE

The Tesys VARIO disconnect switch offers efficient control for ON/OFF operations, with a 63 A capacity and IP65 protection rating, ideal for demanding environments. Its design allows for easy installation and safe handling thanks to its lockable handle, ensuring durability and reliable operation.

[View product online](#)

Description

The TeSys VARIO enclosed switch disconnect is a device designed for on/off control in industrial applications. With a rated capacity of 63 A and an IP65 protection rating, this product is suitable for harsh environments, offering high resistance to water and dust. Its design allows for easy operation thanks to a lockable handle, facilitating its use in various situations.

- Range: TeSys
- Function: Preventive maintenance
- Number of poles: 3P
- Control type: Rotary handle
- Rated operating voltage: 690 V AC
- Rated operating current: 57 A (cable type AC-23A at 400 V)
- Rated operating power: 30 kW at 400 V (cable type AC-23)
- Breaking capacity: 640 A at 400 V (cable type AC-21A)
- Mechanical durability: 30,000 cycles
- Protection rating: IP65 according to IEC 60529
- Ambient operating temperature: -20 to 50 °C
- Fire resistance: 960 °C according to IEC 60595-2-1

Specifications

Rated current (A)	63
EAN	3389110543889
Protection	IP65

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

[If you have any questions, contact our support team](#)

Item downloaded on 14 September 2026