

Product sheet

**NSX400H 400A 85 kA 4P IP40
Basic Rack Fixed Mounting for
Current > 0.1 A**

Brand: SCHNEIDER

Reference: IMPO C40H4

The NSX400H basic frame is a device from the ComPacT range, designed for industrial applications requiring precise electrical current control. With a breaking capacity of up to 85 kA and a rated current of 400 A, it ensures robustness and reliability under demanding conditions.

[View product online](#)**Description**

The NSX400H Cutting Block is a new generation ComPacT range device, designed for applications requiring precise control of electrical current. This basic frame offers a robust and efficient solution for energy management in electrical systems, guaranteeing optimal performance under diverse operating conditions.

- Rated current: 400 A at 40 °C
- Rated operating voltage: 690 V AC, 50/60 Hz
- Number of poles: 4P, with neutral position on the left
- Breaking capacity: 85 kA at 240 V AC, 65 kA at 480 V AC
- Disconnecting capacity: Yes, according to Icu
- Control type: Lever
- Mounting: Fixed, with front and downward connection
- Mechanical durability: 15,000 cycles
- Electrical durability: 12,000 cycles at 440 V AC
- Operating ambient temperature: -25 to 70 °C
- Protection rating: IP40, IK07

Specifications

Rated current (A)	400
Curve	K
EAN	3606482003170

No. of poles	4P
--------------	----

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

[If you have any questions, contact our support team](#)

Item downloaded on 23 October 2026