

Product sheet

SCHNEIDER 400A 70kA 4-pole IP40 fixed and electronic circuit breaker

Brand: SCHNEIDER

Reference: IMPO C40H42D400



The Schneider NSX400H circuit breaker, with a rated current of 400 A and a breaking capacity of 70 kA, is designed for AC applications. Its electronic technology provides reliable and efficient protection, adapting to various installation and operating conditions.

[View product online](#)

Description

The NSX400H circuit breaker from the ComPacT range is a device designed to provide efficient protection in high current electrical circuits. With a rated current of 400 A and a breaking capacity of up to 70 kA, this circuit breaker is suitable for AC applications, ensuring reliable performance under various installation conditions.

- Rated current: 400 A at 40 °C
- Rated operating voltage: 690 V AC, 50/60 Hz
- Number of poles: 4P with 4R protected
- Breaking capacity: 100 kA Icu at 220/240 V AC
- Control unit: Micrologic 2.3 with electronic technology
- Mechanical durability: 15,000 cycles
- Electrical durability: 12,000 cycles at 440 V
- Operating ambient temperature: -25 to 70 °C
- Grade of Protection: IP40, IK07
- Dimensions: 185 mm (width) x 255 mm (height) x 110 mm (depth)
- Weight: 7.9 kg

Specifications

Rated current (A)	400
EAN	3606482002852
No. of poles	4P

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

[If you have any questions, contact our support team](#)

Item downloaded on 9 October 2026