

Product sheet

ECOSTRUXURE 24V DC gateway and data logger with 3-year recording and IP40

Brand: SCHNEIDER

Reference: IMPO PAS800L

The EcoStruxure Panel Server Advanced is a 24V DC data gateway and logger that allows the connection of Modbus/RS485 and Modbus/TCP devices. Its intuitive configuration via integrated web pages facilitates the analysis of historical data and the management of alarms in energy monitoring systems.

[View product online](#)

Description

The EcoStruxure Panel Server Advanced is a Modbus data logger and gateway designed to operate at 24V DC, enabling efficient connection of Modbus/RS485 and Modbus/TCP devices. This device stands out for its ability to facilitate integration with monitoring software and cloud platforms, optimizing data management and analysis through intuitive configuration via embedded web pages.

- Range: EcoStruxure
- Product Type: Gateway and Data Logger
- Power Supply: 24 V DC
- Connections: 2 RJ45 for Ethernet and terminal block for RS485
- Communication Protocols: Modbus TCP, DHCP, HTTPS, NTP/SNTP, IPv4, IPv6
- Logging Capacity: Up to 3 years of historical data
- Supports up to 32 Modbus RTU devices and 128 Modbus TCP/IP devices
- Operating Temperature Range: -25 to 70 °C
- Protection Rating: IP40 (front), IP20 (surround)
- Mounting: DIN rail

Specifications

EAN	3606481014351
Protection	IP40
Nominal voltage (V)	24V

If you have any questions, [contact our support team](#)

Item downloaded on 17 October 2026