

Product sheet



COMPACT NSX interface module, Modbus hub, 24 V DC, 35 mm DIN rail mounting

Brand: SCHNEIDER

Reference: IMPO LV434224

The Compact NSX interface module, Modbus SL HUB, enables daisy-chain communication for Modbus SL devices. Designed for integration with the Compact NSX range, it offers easy DIN rail mounting and operates over a wide temperature range, ensuring reliability in diverse environmental conditions.

[View product online](#)

Description

The Compact NSX Interface Module, Modbus SL HUB, is a concentrator designed to facilitate daisy-chain communication between Modbus SL devices. This device is part of the new generation of ComPacT NSX products, offering an efficient and reliable solution for electrical system integration.

- Product range: ComPacT NSX400...630
- Device abbreviation: Modbus SL HUB
- Product type: Modbus concentrator
- Function: Daisy-chain communication for Modbus devices
- Compatibility: ComPacT NSX100, NSX160, NSX250, NSX400, NSX630
- Communication network type: Modbus, serial line slave (9.6...38.4 kbauds)
- Mounting method: By clips on 35 mm DIN rail
- Nominal supply voltage: 24 V DC
- Current consumption: 2 mA at 24 V DC
- Connections: RJ45 connector
- Certifications: UL
- Dimensions: 102 mm (height) x 71 mm (width) x 18 mm (depth)
- Weight: 57.6 g
- Operating temperature range: -25...55 °C
- Relative humidity: 5...85% at 55 °C non-condensing

Specifications

EAN	3606487034896
Cable cross-section (mm²)	35
Nominal voltage (V)	24V

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, [contact our support team](#)

Item downloaded on 28 October 2026