

Product sheet

ABS Connector for Energy Saving Systems 115 mm

Reference: GSC 404005008



The ABS connector for energy saving systems of 115 mm is an essential component in optimizing energy consumption in electrical installations. Made from ABS material, this connector offers adequate resistance to a maximum pressure of 8 bar, making it ideal for applications that require efficient fluid handling. Its design allows for easy installation and connection in electrical systems, ensuring prolonged durability and optimal performance. This product is compatible with various installation configurations, making it a versatile option for industry professionals. Its diameter of 115 mm ensures proper adaptation to standard pipes, facilitating its integration into energy saving and sustainability projects. Additionally, its cardboard packaging with a hook ensures proper presentation and efficient storage.

[View product online](#)

Description

The ABS connector for energy saving systems of 115 mm is a key element in improving energy efficiency in electrical installations. This component is designed to provide a secure and durable connection in systems that require precise fluid handling. Its construction from ABS material provides notable resistance to pressure, with a maximum limit of 8 bar, making it suitable for various industrial and commercial applications. This connector not only facilitates installation but also contributes to sustainability by optimizing the consumption of energy resources.

Technical Features

Material: ABS

Diameter: 115 mm

Maximum Pressure: 8 bar

Functions: 5

Packaging: Cardboard with hook

Among the benefits of using this connector are its high resistance and durability, which reduce the need for frequent replacements and minimize maintenance costs. Additionally, its optimized design allows for quick and easy installation, saving time and effort for professionals during assembly. As a component of an energy saving system, it contributes to reducing operational costs and complying with environmental regulations, resulting in a positive impact both economically and ecologically. This connector is ideal for applications in plumbing, heating, and cooling systems, where efficiency and safety are paramount. Its ability to withstand high pressures makes it suitable for installations in industrial and commercial environments, where reliability is an essential requirement. Furthermore, its versatility allows for use in renovation and new construction projects, adapting to different needs and technical specifications. The installation of the ABS connector is a straightforward process that can be carried out by professionals.

with experience in the field.

Specifications

EAN	8433373093782
Material	ABS
Measures	115 cm

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 20 October 2026