

Product sheet

Reduced Polyethylene Fitting Link Ø 25 - 20 mm

Brand: WOLFPACK LINEA PROFESIONAL

Reference: AFT 04117436



The Reduced Fitting Link Ø 25 - 20 mm is an essential component in agricultural polyethylene piping systems, designed to connect pipes of different diameters, specifically from 25 mm to 20 mm. Made from high-quality polyethylene, this fitting ensures a secure and durable connection, minimizing the risk of leaks. With a length of 129 mm and a diameter of 57 mm, this product is ideal for applications requiring diameter adaptations in pipes. Its robust and efficient design allows for easy and quick installation, making it a preferred choice for professionals in the agricultural sector. This fitting link is versatile and can be used in various irrigation and water distribution configurations, ensuring optimal and continuous flow in installations.

[View product online](#)

Description

The Reduced Fitting Link Ø 25 - 20 mm is a fundamental accessory for connecting polyethylene pipes in agricultural irrigation systems. This product is specifically designed to facilitate the joining of pipes with different diameters, allowing for an efficient transition between 25 mm and 20 mm pipes. Made from polyethylene, a material known for its corrosion resistance and durability, this fitting is ideal for agricultural environments where exposure to various elements can be a critical factor. Its compact and functional design ensures that the integrity of the piping system is maintained, preventing leaks and guaranteeing a continuous flow of water.

Technical Features

- Inlet diameter: 25 mm
- Outlet diameter: 20 mm
- Total length: 129 mm
- Material: Polyethylene
- Pressure resistance: 12.9 bar
- Temperature resistance: up to 60°C

Among the benefits of using the Reduced Fitting Link is its ability to adapt to different pipe configurations, allowing installers to make modifications to the system without the need to replace entire sections. Additionally, its manufacture in polyethylene ensures a long lifespan, reducing the need for frequent maintenance and associated costs. This fitting is also lightweight, making it easy to transport and install, allowing agricultural professionals to work more efficiently. The applications of this fitting are diverse, being especially useful in drip irrigation systems, where precision in water

distribution is crucial. It can also be used in drinking water installations and drainage systems, where a secure connection between pipes of different diameters is required.

Specifications

High	12.9
Width	5.7
EAN	8435450483707
Long	129 mm
Material	Polietileno

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

[If you have any questions, contact our support team](#)

Item downloaded on 27 October 2026