

Product sheet

Stainless Steel Flexible Coupling 20 cm

Brand: TAQ

Reference: EDM 01460

Sanitary female-female stainless steel flexible coupling DN8x12, internal diameter $\varnothing 6$ mm, length 20 cm, maximum flow rate 28 l/min, maximum pressure 3 bar, operating temperature up to 70 °C.

[View product online](#)

Description

Sanitary female-female stainless steel flexible coupling with a length of 20 cm and an internal diameter of 6 mm, made from high-quality stainless steel for applications requiring corrosion resistance and compliance with sanitary regulations. Designed for quick and secure connections, it offers flexibility without compromising the quality of the transported fluid.

Technical Specifications

- Material: Sanitary Stainless Steel
- Connection Type: Female-Female (DN8x12)
- Internal Diameter: $\varnothing 6$ mm
- Length: 20 cm
- Maximum Flow Rate: 28 l/min
- Maximum Pressure: 3 bar
- Maximum Temperature: 70 °C

Its construction from stainless steel ensures durability and ease of cleaning, making it suitable for both industrial and domestic installations. It provides reliable performance in systems where safe potable water supply is required.

The female-female connection allows quick installation without the need for additional tools, facilitating maintenance and replacement in existing systems. It is especially useful in applications that demand flexibility and sanitary compatibility.

Specifications

Diameter	6 mm
EAN	8429343087622
Manufacturer	TAQ
Long	20

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, [contact our support team](#)

Item downloaded on 7 October 2026