

Product sheet

Ground HSS Drill 1 mm Diameter

Brand: BLUEMASTER

Reference: EDM 16003



Rectified HSS drill according to DIN 338, diameter 1.00 mm, point 118°, helix type N 30°. Designed for precise drilling in steels and general metals up to 70 kg/mm² of resistance.

[View product online](#)

Description

High-speed ground drill (HSS) according to DIN 338 standard, with a diameter of 1.00 mm, sharp point at 118° and N-type helix of 30°. Designed for precise drilling in steels and general metals up to a resistance of 70 kg/mm². Its HSS construction ensures high wear resistance and extended service life.

Technical Features

- Diameter: 1 mm
- Material: HSS (High Speed Steel)
- Point Angle: 118°
- Helix Type: N 30°
- Standard: DIN 338
- Quantity: 2 units

This drill delivers optimal performance in industrial applications where precision and durability are required. It is especially suitable for drilling operations in manual or conventional machine tool environments.

It is recommended to use it by adjusting the speed and feed according to the specifications of the processed material, ensuring a clean and efficient cut during the drilling process.

Specifications

Diameter	1 mm
EAN	8422798615112

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, [contact our support team](#)

Item downloaded on 13 October 2026