

Product sheet

SDS Wall Crown 40 mm

Brand: WOLFPACK LINEA PROFESIONAL

Reference: AFT 09112255



SDS Wall Crown 40 mm for installation of lighting in structural walls. Diameter 40 mm, tensile strength 1200 N/mm², compatible with SDS system.

[View product online](#)

Description

The SDS Wall Crown 40 mm is an accessory designed for the installation of lighting systems in walls, compatible with LED and low-energy technologies. Its construction from reinforced polycarbonate ensures long-lasting durability in indoor or outdoor environments exposed to moderate weather conditions.

Technical specifications

- Diameter: 40 mm
- Material: Reinforced polycarbonate
- IP Rating: IP65
- Compatibility: SDS System

This crown provides an efficient solution for protecting cables and connections in vertical electrical installations. Its design allows easy maintenance and facilitates access to internal components without the need for additional tools.

It is recommended for use in architectural, decorative or functional lighting applications in commercial, residential and public spaces. Installation is done by direct mounting on the wall with provided screws, ensuring a secure and stable mount.

Specifications

Diameter	40 mm
Size of the mouth	40
EAN	8435450477195
Material	Policarbonato reforzado
Protection	IP65

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 15 October 2026