

Product sheet



Compact Flame-Retardant Polyurethane Foam 750ml Spray

Brand: ALFA

Reference: ALFA 49886

750ml manual spray pack with flame retardant monocomponent foam and high thermal resistance. Dry product sandable or paintable to mount, seal, isolate and fill holes in construction materials. Universal adherence to various substrates with easy placement and controlled expansion.

[View product online](#)

Description

The 750ml compact flame retardant polyurethane foam is a monocomponent insulation designed to seal, mount and isolate holes in construction structures by means of controlled expansion.

Technical characteristics

- Capacity: 750ml
- Type: Single component expansion foam
- Property: Ignifugal and resistant to high temperatures
- Accession: Compatible with all types of materials
- Finished: Sandable and paintable after drying

This product offers an effective thermal and acoustic insulation, guaranteeing the tightness of the joints in walls, ceilings and floors without compromising the final aesthetic. Their resistance to fire contributes to the passive security of the building.

The installation is simple by applying the spray manually over the area to be treated, allowing the foam to automatically fill the voids until the desired volume is reached. It is ideal for filling holes in door frames and windows or sealing together on facades.

Management requires protecting the skin and airways during application. After complete drying, the

surface can be gently sanded or painted with any type of varnish or conventional paint to visually integrate with the construction environment.

Specifications

EAN	8425160498863
Weight (kg)	1.0833

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 12 September 2026