Product sheet

Round White LED Surface Mount 480mm 45W CCT

Brand: ALFA

Reference: ALFA 28385

Apply round 480mm and 45W LED with ABS+PS flame retardant housing and acrylic panel. It offers 4050 lumens, IP44 outdoor protection and integrated CST selector. A beam angle greater than 120o guarantees uniform lighting on facades or corridors with instant electronic ignition and high light performance.

View product online

Description

This 45W round surface LED applicator offers an efficient and durable light solution for outdoor spaces. With a diameter of 480mm and CST technology, it provides versatile lighting that adapts to various environmental needs through its high quality acrylic light panel.

Technical characteristics

- Power: 45W
- Luminosity: 4050 lumens
- Diameter: 480mm
- Housing material: ABS+PS flame retardant
- Light panel: Acrylic LED
- Energy classification: F
- Protection: IP44
- Opening angle: 120° minimum
- Functionality: CCT selector (cold, neutral, warm)
- On: Instant Electronics

Its high light performance and the ability to adjust the color temperature make it a superior choice to enhance facades, main entrances or terrace areas. The robustness of the flame retardant material ensures safety and longevity against adverse weather conditions.

The installation is simple thanks to its surface design and protection grade suitable for outdoors. It is recommended to fix the device on vertical walls or flat ceilings, ensuring a correct electrical connection before activating the color temperature switch.

Specifications

High	Redondo
Opening angle	120
Energy classification	F
Colour	White
Diameter	480 mm
Diameter embedment (mm)	480
Driver included	Yes
EAN	8425160283858
Lumens (lm)	4050
Material	ABS
Weight (kg)	1.507
Protection	IP44
Nominal voltage (V)	180-240
Shape	Round

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 3 November 2026