

Product sheet

2P+TT Socket Base with Shutter 16A 250V White

Brand: SOLERA

Reference: SOLERA ERP60U



2P+TT socket base with safety shutter, 16A rated current and 250V voltage. Made of halogen-free thermoplastic with silver contacts for high rupture. Screw connection, integrated child protection and dimensions 83x81mm. Embedded cast mounting.

[View product online](#)

Description

The 2P+TT plug base with shutter is an electrical connection device designed to ensure safety and reliability in fixed installations. It operates at a nominal voltage of 250 V and a current of 16 A, adapting perfectly to residential and commercial environments that require a stable supply. Its automatic shutter mechanism protects contacts against accidental access, preventing short circuits and injuries. This component is integrated by embedded cast mounting, offering a robust and durable solution for the distribution of energy in electrical panels.

Technical characteristics

- Nominal voltage: 250 V
- Nominal current: 16 A
- Frequency: 50...60 Hz
- Dimensions: 83 mm wide x 81 mm high
- Material: Halogen-free thermoplastic
- Area: Brilliant, white
- Connection type: Screwed terminal (screw)
- Degree of protection: IP20
- Contacts: Silver high breaking power
- Child protection: Yes

The technical features of this plug ensure optimum performance and high breaking capacity thanks to the silver contacts. The use of halogen-free thermoplastic material ensures that, in case of fire, no toxic

gases are released, improving the overall safety of the installation. Protection against children prevents access to exposed terminals, complying with existing safety regulations and protecting the most vulnerable users.

The installation is simple by means of a hook and screw system that allows you to firmly attach the device to the cast box. Once mounted, the shutter automatically closes when removing the connector, ensuring that no exposed metal parts remain.

Specifications

High	8.3
Rated current (A)	16
Width	8.1
Colour	White
EAN	8423220076983
Material	Plástico
Measures	8.3 x 8.1
Protection	IP20
Nominal voltage (V)	250V

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

[If you have any questions, contact our support team](#)

Item downloaded on 28 October 2026