

Product sheet

Puncture-proof wheel ø360 mm expanded polyurethane solid steel

Reference: EDM 87181



Impinchable castor with expanded polyurethane tread and single-block steel rim. It has a 20 mm shaft, a total measurement of 360 mm and a 240 mm bushing width. It supports a maximum load of 75 kg thanks to its robust design and footprint pattern in lines for greater traction.

[View product online](#)

Description

The impinchable wheel features an expanded polyurethane tread, designed to withstand a maximum load of 75 kg with a total diameter of 360 mm. Its construction includes a single-block steel rim and a 20 mm diameter shaft.

Technical characteristics

- Type: Impinchable wheel
- Axle: Ø20 mm
- Wheel measure: Ø360 mm
- Rim: Of single-block steel
- Bearing width: 240 mm
- Rolling strip: Of expanded polyurethane
- Maximum load: 75 kg
- Footprint pattern: Lines
- Rolling width: 80 mm

The line pattern in the tread and the width of 80 mm define its contact profile with the ground.

Specifications

Diameter	36 cm
----------	-------

EAN	8435427919277
Manufacturer	CASCOO
Long	24
Measures	Ø360 x 240 mm
Depth	8

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

[If you have any questions, contact our support team](#)

Item downloaded on 26 September 2026