

Product sheet

Lifud Driver 220-240V DC 40W No Flicker

Brand: Lifud

Reference: LEDME LF-GIF040ES-1050H



Lifud driver with controlled 20-42V DC output, maximum power of 42W, compatible with AC 100-277V power supply. Designed to operate in temperature ranges from -30°C to +50°C, with 0.9 power factor and IP20 protection. Includes overvoltage (4 kV), overload and short circuit protection.

[View product online](#)

Description

Lifud driver with 220-240V DC 40W output, designed for LED lighting applications with no blinking operation. Compatible with 100-277V AC input voltages, it offers a stable 20-42V DC output and a 1050 mA current. Its compact design and PC material makes it suitable for industrial or commercial environments with extreme temperature conditions.

Technical characteristics

- Maximum power: 42 W
- Working temperature: -30°C ~ +50°C
- Protection: IP20
- Overvoltage protection: 4 kV
- Overheating protection: no
- Overload Protection: Yes
- Short circuit protection: Yes
- Power supply: 100-277 V AC
- Departure: 20-42 V DC
- Current Intensity: 1050 mA
- Dimension: 98 x 40.5 x 25.5 mm
- Material: PC
- Power Factor: 0.9
- Guarantee: 5 years

Specifications

Manufacturer	Lifud
Material	PC
Measures	98X40,5X25,5H mm
Maximum power (W)	42 W
Protection	IP20
Nominal voltage (V)	100-277 V

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 10 October 2026