

Product sheet

Lifud DALI/PUSH Dimmable Driver 20-42V DC 21W

Brand: Lifud

Reference: LEDME LF-ADD020-0500-42



Driver Lifud with DALI/PUSH adjustable output, maximum power 21 W, output 20-42 V DC, current 350-500 mA. Power supply 100-277 V AC, power factor 0.9. IP20 protection, resistant to surges of up to 4 kV. It works in temperature ranges from -30°C to +50°C. Built of PC material, with protection against overload and short circuit.

[View product online](#)

Description

Lifud driver with adjustable 20-42V DC output, maximum power of 21W, designed to control LED lighting using DALI protocol or push signal. Compatible with 100-277V AC power supply, it offers a power factor of 0.9 and an output current between 350-500 mA. Its design in PC material and IP20 protection makes it suitable for controlled interior environments.

Technical characteristics

- Maximum power: 21W
- Power supply: 100-277V AC
- Departure: 20-42V DC
- Current Intensity: 350-500 mA
- Power Factor: 0.9
- Regulatory: DALI/PUSH
- Working temperature: -30°C ~ +50°C
- Protection: IP20
- Overvoltage protection: 4 kV
- Overload Protection: Yes
- Short circuit protection: Yes
- Overheating protection: No
- Material: PC

- Dimension: 121.9 x 39.9 x 25 mm
- Guarantee: 5 years

Specifications

Manufacturer	Lifud
Material	PC
Power (W)	21 W
Protection	IP20
Adjustable	Yes
Nominal voltage (V)	100-277 V
Current type	AC

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

[If you have any questions, contact our support team](#)

Item downloaded on 9 October 2026