

Product sheet



Desan Recessed LED Beacon 7W CCT IP65

Brand: LEDME

Reference: LEDME LM6166

The 7W Desan recessable LED beacon integrates Epistar diodes with 560 lumen luminance and 80 lm/W efficiency. Its aluminium housing ensures IP65 protection and IK8 resistance, operating between -20°C and +45°C. It has a 120° beam angle, CRI 80 index and 40000 hours service life with 220-240V power supply.

[View product online](#)

Description

The M LEDME brand LED Desan recessable beacon is a luminous device designed to provide efficient and durable lighting in spaces requiring color temperature control. Its integrated technology ensures optimal performance under various environmental conditions.

Technical characteristics

- Mark: M LEDME
- Power: 7 W
- Light source: Epistar
- Luminosity: 560 lm
- Efficiency: 80 lm/W
- Working temperature: -20°C ~ +45°C
- Emission angle: 120°
- Lifetime: 40,000 hours
- Protection: IP65
- Impact class: IK8
- Insulation class: I
- Power supply: 220-240V AC
- Material: Aluminium
- CRI: 80
- CCT options: 3 color temperatures

- Dimensions: 165x105x65 mm
- Cutting dimensions: 157x97 mm
- Includes: Mounting box
- Guarantee: 3 years

Thanks to its aluminium construction and IP65 protection, this equipment maintains its functionality in demanding environments, ensuring a long service life without the need for frequent maintenance for decades.

Specifications

Appliance class	Class I
Cri (Ra)	80
EAN	8435579761663
Manufacturer	Ledme
Lumens (lm)	560 lm
Material	Aluminio
Power (W)	7 W
Protection	IP65
Nominal voltage (V)	220-240 V
Estimated life (h)	40000

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 29 September 2026