Product sheet



M LEDME Soft 18W CCT Surface LED Panel with Sanan Driver

Brand: LEDME

Reference: LEDME LM8302

18W Surface LED Panel with CCT technology and Sanan driver, delivering 1620 lumens and 90 lm/W efficiency. Features a CRI of 80, 120º beam angle, and 30,000-hour lifespan. Safe operation between -20°C and 45°C, power factor 0.9, and surface installation in PC.

View product online

Description

The M LEDME Soft 18W Surface LED Panel is a lighting device designed to provide an efficient and durable luminous solution. Its polycarbonate (PC) construction and Sanan light source ensure stable performance under various environmental conditions.

Technical Specifications

- Watts: 18 w
- Luminous Flux: 1620 lm
- Efficiency: 90 lm/W
- Operating Temperature: -20°C ~ +45°C
- Beam Angle: 120º
- Lifespan: 30,000 hours
- Protection: IP20
- Electrical Insulation Class: II
- Supply Voltage: 220-240v ac
- Dimensions: 220X21H mm
- Materials: PC
- CRI: 80
- Power Factor: 0.9
- Warranty: 3 years
- Color Temperature: 5CCT

With an extended lifespan of 30,000 hours and a CRI of 80, this panel maintains consistent light quality throughout its operational cycle. Its surface installation allows for easy integration into flat ceilings, utilizing its 120-degree angle to distribute light evenly in standard indoor spaces.

Specifications

Appliance class	Class II
Opening angle	120º
Cri (Ra)	80
EAN	8435579783023
Manufacturer	Ledme
Lumens (lm)	1620 lm
Material	PC
Measures	220X21H mm
Power (W)	18 W
Protection	IP20
Estimated life (h)	30000

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 25 November 2026