

Product sheet

Lifud Adjustable Dali Driver 30W 9-42V DC

Brand: Lifud

Reference: LEDME LF-ADD030-0750-42



Lifud adjustable driver with DALI control and push, DC 9-42V continuous output, adjustable current between 400-750 mA, maximum power of 32 W, power factor 0.9, AC 100-277 V power supply, operating temperature -30°C to +50°C, IP20 protection, made of polycarbonate (PC), dimensions 144x46x28 mm, 5-year warranty.

[View product online](#)

Description

Lifud adjustable driver with Dali and Push control, designed to power LED luminaires with 9-42V DC output. Compatible with DALI control systems and push-button, it offers an output up to 30W with an adjustable current intensity between 400-750 mA. Its wide power range (100-277V AC) allows use in multiple electrical environments. It works in temperatures from -30°C to +50°C, with IP20 protection, ideal for indoor installations. Made of PC material, it presents a power factor of 0.9 for energy efficiency. Includes 5 year warranty.

Technical characteristics

- Maximum power: 32 W
- Working temperature: -30°C ~ +50°C
- Protection: IP20
- Power supply: 100-277 V AC
- Exit: 9-42 V DC
- Current Intensity: 400-750 mA
- Dimension: 144 x 46 x 28 mm
- Material: PC
- Power Factor: 0.9
- Regulatory: Dali
- Guarantee: 5 years

Specifications

Rated current (A)	0.75
Manufacturer	Lifud
Material	PC
Measures	144x46x28H mm
Maximum power (W)	32W
Protection	IP20
Adjustable	Yes
Nominal voltage (V)	100-277V
Current type	AC

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, [contact our support team](#)

Item downloaded on 6 October 2026