Product sheet



Circular LED Panel Series Pro 5W CCT iSG Lighting

Brand: LEDME

Reference: LEDME GA5620

The iSG Lighting Series Circular Led Panel integrates the Ledvance Light source to provide a 500 lumen luminance with 100 lm/W efficiency. Designed in aluminium and polycarbonate, it operates between -20°C and +45°C with 120° angle and 30000 hour life under 170-265v ac power supply.

View product online

Description

The iSG Lighting Pro Series Circular Led Panel is a recessable lighting device designed to deliver efficient and durable light performance, integrated with optional adjustable CST technology.

Technical characteristics

- Watts: 5 w
- Light Source: Ledvance
- Luminosity: 500 lm
- Efficiency Lm: 100
- Working temperature: -20°C ~ +45°C
- Angle: 120°
- Useful Life: 30000 hours
- Protection: IP20
- Ik: 5
- Class Electrical insulation: II
- Power supply: 170-265v ac
- Dimension: 85X10H mm
- Cut dimension: 75 mm
- Material: Aluminium
- Driver: Lifud
- Cri: 80

- Ugr: <19
- Regulatory: Optional
- Guarantee: 5 years
- Color Temperature: 3CCT

With high light efficiency and a chromatic reproduction index of 80, this panel ensures clear and uniform lighting with low glare (Ugr <19), suitable for spaces that require precise light control.

The recessable installation allows discreet integration into ceilings, taking advantage of its compact circular design and aluminium and polycarbonate materials for stable thermal dissipation within the specified operating range.

Specifications

Appliance class	Class II
Opening angle	120°
Cri (Ra)	80
EAN	8435579756201
Manufacturer	iSG Lighting
Lumens (lm)	500 lm
Power (W)	5 W
Protection	IP20
Estimated life (h)	30000

This document is based on the product page published in our store and is provided for information only. It is not contractual. It may contain errors or omissions and does not replace the manufacturer datasheet.

If you have any questions, contact our support team

Item downloaded on 25 November 2026